

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- GLASS SHADING

REFERENCE:- W/454/1

COLOUR:- WHITE

FINISH:- MATT

TYPE:- AQUEOUS MIXED POLYMER
DISPERSION

TYPICAL SG:- 1.70 AT 20°C

TYPICAL VISCOSITY:- PASTE

TYPICAL TOTAL SOLIDS:- 70%

FLASH POINT:- NON-FLAMMABLE

RECOMMENDED THINNERS:- WATER

APPLICATION:- BRUSH OR ROLLER. THIN AS
APPROPRIATE WITH WATER
DO NOT APPLY WHEN THE
TEMPERATURE IS BELOW 5°C

*COVERAGE GUIDE:- DEPENDANT ON PERCENTAGE
ADDED WATER

*DRYING TIME:- 1-2 HOURS. COLD, DAMP
CONDITIONS WILL PROLONG
THE TIME.

STORAGE:- PROTECT FROM FROST AND
ABNORMAL HEAT.

HEALTH & SAFETY DATA:- SEE SDS 10628

*BY BRUSH TO A DRIED FILM THICKNESS OF 20-25 MICRONS AT 20°C.

COO-VAR

PAINTS, PRIMERS & SPECIALISED COATINGS

Ellenshaw Works, Lockwood Street, HULL. HU2 0HN
Telephone : 01482-328053 Fax: 01482-219266