

PRODUCT DATA SHEET

No. 10485

JANUARY 2005

RONSEAL ONE COAT TILE PAINT

Ronseal One Coat Tile Paint is formulated to provide a tough and durable finish to ceramic tiles and is ideal for use in most interior domestic environments. No primers are required and tiled surfaces can be transformed without the need for re-tiling. Ronseal One Coat Tile Paint forms a highly waterproof coating, in one application, making it especially suitable for kitchens and bathrooms.

INTRODUCTION

Ronseal One Coat Tile Paint is a tough, durable and waterproof solvent based polyurethane alkyd finish designed to transform and provide a waterproof coating to ceramic tiles in one application. No primers are required and unsightly tiles can be transformed without the cost and disruption associated with re-tiling.

Ronseal One Coat Tile Paint is suitable for most domestic situations but the highly waterproof coating makes it particularly suitable for kitchens and bathrooms. Ronseal One Coat Tile Paint will transform most surfaces with a single coat and dries to a smooth sheen finish free from brush marks.

Ronseal One Coat Tile Paint has excellent sag resistance ensuring it does not sag or run during application. It also contains fungicide for the purpose of preserving the coating against mould and fungal growth.

COMPOSITION

Ronseal One Coat Tile Paint is a dispersion of resins, pigments, extenders and colouring agents in hydrocarbon solvent.

PROPERTIES

Appearance – Coloured low to medium viscosity liquid.

Odour – Characteristic solvent type.

VOC content- High (25-50% w/v)

Flammable.

Immiscible with water.

FIELDS OF APPLICATION

Ronseal One Coat Tile Paint is suitable for most tiled surfaces in a domestic environment including splash areas around sinks, baths and cookers and shower areas (see 'IMPORTANT NOTES').

Ronseal One Coat Tile Paint is not recommended for use floor tiles (including those in showers) or tiled work surfaces.

PREPARATION

Ensure surfaces are clean, dry and free from grease, detergent, dust and other surface contaminants.

Clean tiled areas thoroughly with a household cleaner containing bleach, rinse thoroughly and wipe down. Avoid using paper towels or cloths which leave fibres.

It is advisable to clean grouting with a scrubbing brush or nail brush, particularly if black mould is present. Damaged grouting should be repaired. Allow grouting to dry thoroughly before treating with Ronseal One Coat Tile Paint.

APPLICATION

Stir well prior to and during use. Do not thin.

For best results apply with a good quality natural bristle brush. Work the product well into grouting lines to ensure good coverage, but avoid a build up of product as this may lead to runs. Finish in the same vertical direction on each tile.

A second coat may be required where a major colour change is involved or where tiles are heavily patterned.

MAINTENANCE

Surfaces coated with Ronseal One Coat Tile Paint should be cleaned with mild detergent. Do not use abrasive cleaners.

COVERAGE

8 square metres per litre.

DRYING TIME

Touch dry in 1 to 2 hours. Overcoat after 16 hours if required.

Allow 24 hours before redefining grout lines with Ronseal One Coat Grout Pen.

Low temperatures, poor ventilation and high humidity will lengthen dry and re-coat times.

CLEANING OF TOOLS

All tools and equipment should be cleaned immediately after use in white spirit or brush cleaner.

Remove as much product as possible from tools and equipment before washing.

IMPORTANT NOTES

Apply in accordance with the coverage guidelines otherwise product performance will be reduced. Always read the instructions carefully before use.

Avoid prolonged contact with water for 72 hours after application to allow the product to fully cure. Treated shower areas should be kept completely dry and free from humidity for at least 48 hours. The product will not reach its maximum hardness for several days. During this period wipe off water/splashes immediately after use.

Always test the colour on a small inconspicuous area to confirm acceptability prior to use.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition and direct sunlight.

Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers is at least three years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Contains Cobalt Carboxylate, EMKO; may produce an allergic reaction.

Flammable.

Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Repeated exposure may cause skin dryness or cracking.

Wear suitable gloves.

If swallowed seek medical advice immediately and show this container label.

Use only in well ventilated areas.

Avoid release to the environment.

Keep away from sources of ignition.

No Smoking.

Keep out of reach of children.

Refer to special instructions/safety data sheets.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flammable.
Flash point 23-61°C.

SUPPLY

Obtainable from selected DIY retailers.

SIZES

Available in a 750ml re-sealable container.

DISPOSAL

Remove as much product as possible from brushes prior to cleaning.

Some local authorities have special facilities for the disposal or dispensing of waste coatings.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,

**Thornclyffe Park
Chapelton
Sheffield
S35 2YP**

**Tel:
+44 (0114) 240 9469 (Technical Services)
+44 (0114) 246 7171 (Main Switchboard)**

**Fax:
+44 (0114) 245 5629**

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a registered trademark of the Sherwin Williams Company.

JANUARY, 2005. ISSUE 1