

## DESCRIPTION

A solvent-borne blend of fine grade aluminium and high quality resin. Formulated for interior and exterior use on new or bare timber it provides a barrier against the oily exudations of naturally resinous timber and can be used as a sealer on weathered creosote or smoke damaged surfaces and is also self-knotting.

## RECOMMENDED USES



For use on new or bare timber. Seals weathered creosote or smoke damaged surfaces. Primes resinous, scorched and smoke damaged timber and is also self knotting.

## SPECIAL PROPERTIES

Can be used as a sealer on weathered creosote or smoke damaged surfaces.

## COLOUR RANGE

Metallic Grey.

## FINISH

Matt.

## VOLUME SOLID

37%

## COVERAGE



Johnstone's Aluminium Wood Primer will cover at the rate of approximately 13–15 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Recoat after 16–24 hours under normal drying conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

TC2 Thinner and Cleaner.

## VOC CONTENT

HIGH VOC CONTENT 25–50%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 350g/l (2010).  
This product contains max 350g/l VOC.

## FILM THICKNESS

Wet: 75µm, dry: 28µm.

## SIZE

1 Litre, 2.5 Litre and 5 Litre.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Wash down oily timbers such as teak with White Spirit and allow to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

## APPLICATION



Stir well before use. Easy to apply by brush paying particular attention to the end grain.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC2 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- WARNING
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.