

## DESCRIPTION

A durable acrylic resin based mould inhibiting coating for use on walls and ceilings to protect against algal and fungal growth. Dries to a smooth, matt finish.

## RECOMMENDED USES



In areas where conditions are conducive to mould growth, eg. food preparation areas and bathrooms. Use only in accordance with the directions on the label. For interior use.

## SPECIAL PROPERTIES

Quick drying anti-mould properties, durable and washable.

## COLOUR RANGE

Brilliant White, Magnolia and a range of colours via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

30%.

## COVERAGE



Johnstone's Anti-Mould Acrylic will cover at the rate of approximately 9–11 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 4-6 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

MINIMAL VOC CONTENT 0-0.29%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 140g/l (2010).  
This product contains max 3g/l VOC.

## FILM THICKNESS

Wet: 100µm, dry: 30µm.

## SIZE

2.5 Litre and 5 Litre

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Wear a suitable face mask when dry sanding. Surfaces already contaminated with mould growth should be treated with Johnstone's Sterilisation Wash as directed. For further advice contact Technical Advisory: 01924 354354.

## APPLICATION



Stir well before use. Suitable for application by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Anti-Mould Acrylic thinned with up to 10% clean water. Do not apply in temperatures below 5°C or externally when rain is imminent.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

### Statutory conditions relating to use

- FOR USE ONLY AS A BIOCIDAL PAINT.
- APPLY AT A RATE OF ONE LITRE PER 9-11 SQUARE METRES (DEPENDANT UPON SURFACE POROSITY) by brush, roller or spray.
- Wear suitable protective clothing and gloves.
- Do not breathe spray. Otherwise wear respiratory protective equipment and eye protection (see HSE Guidance Booklet HS (G) 53 "The Selection, Use and Maintenance of Respiratory Protective Equipment - A Practical Guide).
- Use only in well ventilated areas.
- DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.
- Do not empty into drains.
- DO NOT USE NEAR DRAINS.
- PREVENT ANY SURFACE RUN-OFF FROM ENTERING DRAINS.
- COVER WATER STORAGE TANKS before application.
- This material and its container must be disposed of in a safe way.
- DANGEROUS TO FISH AND OTHER AQUATIC LIFE.
- REMOVE OR COVER ALL FISH TANKS AND BOWLS before application.
- Do not contaminate ground or watercourses with chemicals or used container.
- KEEP AWAY FROM TREATED SURFACES UNTIL DRY.

- **Read all precautions before use (HSE No.7364).**
- WASH ANY CONTAMINATION from skin or eyes immediately.
- WASH HANDS AND EXPOSED SKIN before meals and after use.
- Keep only in original container.
- Keep container tightly closed.
- KEEP IN A SAFE PLACE.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.
- CONTAINS DICHLOROPHENYL DIMETHYULUREA 0.220% W/W.  
CABENDAZIM 0.099% W/W. 2-OCTYL-2H-ISOTHIAZOL-3-ONE 0.031% W/W.
- This product is approved under The Control of Pesticides Regulations 1986 for use as directed (HSE No.7364).