

DESCRIPTION

Woodworks Heavy Duty Yacht Varnish has been specially formulated for use on all exterior smooth planed timber, doors and window frames. A traditional marine quality varnish, it provides a flexible varnish film that flexes with the timber surface.

AVAILABLE IN

750ml, 2.5 litre and 5 litre sizes.

COLOUR RANGE

Clear Gloss.

RECOMMENDED USES



Suitable for exterior use.

TYPES OF SUBSTRATE

Doors, window frames and all smooth planed exterior timber.

COVERAGE



Approximately 15 square metres per litre depending on the nature and porosity of the surface being varnished.

DRYING TIME



Recoat after 16–24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.
STORE AWAY FROM HEAT AND FLAME.

CLEANER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25-50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.

PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Previously varnished surfaces in sound condition should be rubbed down with fine waterproof abrasive paper and rinsed thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For best results, new or bare wood should be lightly rubbed down along the grain with fine abrasive paper, any knots sealed with a clear knotting solution, treated with a suitable clear Wood Preservative and allowed to dry. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstones Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir Yacht Varnish thoroughly before use. Apply two or more coats of varnish evenly, by good quality brush along the wood grain as required paying particular attention to the end grain. Do not overlap the brush strokes.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Flammable liquid and vapour.
- May cause an allergic reaction.
- Hazardous ingredients: 4,5-dichloro-2-octyl-3(2H)-isothiazolin-3-one.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Wear protective gloves/protective clothing/eye/face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.