

DESCRIPTION

Johnstone's Water Seal is a waterproofing sealer formulated for use on porous exterior walls. It provides a water repellent surface whilst allowing the substrate to breathe without changing the appearance of the substrate. This product is designed only for above ground masonry surfaces. Water Seal will not remedy structural defects.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Clear.

FINISH

Transparent.

VOLUME SOLID

9%

COVERAGE



Approximately 3–5 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Recoat after 8 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

Very high VOC content more than 50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

KEY PROPERTIES

- For use on exterior porous walls.
- Provides a water repellent surface whilst allowing the substrate to breathe.
- Does not change the appearance of the substrate.

PREPARATION

All surfaces to be coated should be clean, dry and free from loose and flaking material. Ensure all cracks are repaired. Avoid the inhalation of dust - wear a suitable face mask. For further advice contact Technical Advisory, on 01924 354354.

APPLICATION



Easy to apply by brush or roller. Apply a generous coat to provide maximum protection.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Flammable liquid and vapour.
- May be fatal if swallowed and enters airways.
- May cause drowsiness and dizziness.
- Toxic to aquatic life with long lasting effects.
- Hazardous ingredients: Naphtha (petroleum), hydrodesulfurised heavy: Nota(s) P.
- Safety data sheet available on request.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Avoid breathing vapour.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Avoid release to the environment.
- Collect spillage.
- IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
- IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do not induce vomiting.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Store in a well-ventilated place. Keep cool.
- Store locked up.

SIZES

5 Litre.