

DESCRIPTION

A pre-treatment for galvanised steel which converts the surface nature to ensure the subsequent adhesion of a wide range of coatings.

RECOMMENDED USES

A pre-treatment for galvanised steel to ensure adhesion of topcoat.

SPECIAL PROPERTIES

Converts the surface nature of galvanised steel.

COLOUR RANGE

Blue.


FINISH

Matt.

VOLUME SOLID

Not applicable.

COVERAGE



Johnstone's Mordant Solution will treat approximately 15 square metres per litre.

DRYING TIME

30 minutes (minimum), 24 hours (maximum).

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Not applicable.

VOC CONTENT

Not applicable.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

SIZE

5 Litre.

PREPARATION

Ensure all oil and grease is removed from the surface to be treated by using Johnstone's Cleaner & Degreaser. Allow the surface to dry before application of subsequent coating.

APPLICATION

Thoroughly work Johnstone's Mordant Solution into the surface using a brush ensuring all the surface changes colour (blackens). If no initial reaction takes place, then a second application may be required. Rinse with clean water and allow to dry.

CLEANING

Not applicable.

PRECAUTIONS

- IRRITATING TO EYES.
- Contains: Propan-2-ol.
- Use only in well ventilated areas.
- Vapours may cause drowsiness and dizziness.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of water.
- Wear suitable protective clothing, gloves and eye/face protection.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

