

DESCRIPTION

Johnstone's Ultra Primer Sealer is a high performance, quick drying, alkali resisting primer sealer manufactured from high quality pigments and tough acrylic resin now with enhanced stain blocking properties. Primes and seals plaster, plasterboard, cement render, timber, bare masonry, interior stone and fibre cement boards, wood panelling, ceramic and glazed tiles, doors, trim, windows and any surface where great adhesion, fast drying, stain blocking properties are needed.

RECOMMENDED USES

Ideal for use in private and public buildings where its low odour properties, combined with ease of application and speed of drying, allow the work to be completed with a minimum of disruption.

SPECIAL PROPERTIES

Primes difficult substrates. Seals porous surfaces.
Stain blocks

COLOUR RANGE

Brilliant White.

FINISH

N/A

VOLUME SOLID

45%

COVERAGE

Johnstone's Ultra Primer Sealer will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Touch dry in 30 minutes.
Recoat after 3 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

LOW VOC CONTENT 0.3-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 30g/l (2010).

This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 45µm.

SIZE

1 Litre, 2.5 Litre and 5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION

Stir well before use. Apply one full coat, brushing firmly into the surface. Porous surfaces should be sealed with a first coat of Ultra Primer Sealer thinned with up to 20% clean water. Allow 3 hours to dry under normal conditions before applying the required paint finish. For best results, apply by brush as this assists the primer to penetrate the surface. Alternatively Ultra Primer Sealer can be applied by airless spray. Allow fresh plaster to dry thoroughly before application. Do not apply when air or surface temperature is below 10°C.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.