

## DESCRIPTION

Johnstone's AirPure is an air purifying wall and ceiling paint that improves indoor air quality. Formulated with a biobased binder and contained in 100% recycled packaging, AirPure is the perfect paint for sustainable projects, where improving the indoor air quality is required.

## RECOMMENDED USES



Suitable for all interior walls and ceilings both bare and previously painted including plaster, plasterboard, concrete, wallcoverings etc.

## COLOUR RANGE

White and pastel colours.

## FINISH

Flat Matt Finish.

## VOLUME SOLID

35%

## COVERAGE



Up to 11m<sup>2</sup> per litre depending on the nature and porosity of the surface.

## DRYING TIME



Touch Dry 1 hour  
Recoat after 4 hours.

## TRANSPORTATION & STORAGE

No more than 8kg (5Ltr).

## THINNER

Clean water.

## VOC CONTENT

MINIMAL VOC CONTENT 0 - 0.29%

VOC (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).  
This product contains max 1g/l VOC.

## FILM THICKNESS

Wet 100 microns and Dry 35 microns.

## KEY PROPERTIES

- Sustainable formulation 45% biobased (ASTM D6866)
- Air purifying technology (ISO 16000-23)
- Improves indoor air quality – by removing up to 70% Formaldehyde
- Flat Matt Finish

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush and roller, also suitable for application by spray. Seal absorbent surfaces such as new plaster, plaster boards, filler etc. with a coat of Air Pure thinned up to 5% with clean water. Do not apply in temperatures below 10°C or in damp conditions.

### SPRAY APPLICATION

Airless spray; un-thinned spray @ 2300psi/159 bar with 517 tip

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Safety data sheet available on request

## SIZES

5 Litre.